


C-ML217VC-II (LM17)

17" VGA/BNC TFT CCTV Monitor



CBC's C-ML217VC-II (LM17) 17" LCD monitor offers excellent picture quality with a wide viewing angle and a sleek casing that maximises desktop space. The C-ML217VC-II is a 17" Active Matrix TFT LCD screen providing an impressively high 1000:1 contrast ratio plus 1280 x 1024 SXGA resolution and a rapid 5ms response time.

This monitor is suitable for any commercial or office application, with an easily removed desk mount allowing it to be fitted with any standard 75mm VESA accessories.

An analogue input, VGA and S-Video capabilities provide various connection options too.

Key Features

- ▶ 1280 (H) x 1024 (V) SXGA Resolution
- ▶ High 1000:1 contrast ratio
- ▶ Wide viewing angle
- ▶ Two (stereo) built-in speakers
- ▶ Multi language OSD
- ▶ Fast 5ms response time
- ▶ Slim bezel casing
- ▶ < 40W power consumption

V1.01

C-ML217VC-II (LM17)

17" VGA/BNC TFT CCTV Monitor

Specifications

Description / Model	C-ML217VC-II (LM17)
MONITOR SPECIFICATION	
Display Type	17" Active Matrix TFT LCD Module
Resolution	1280(H) x 1024(V) SXGA
Pixel Pitch	0.264 (H) x 0.264 (V)
Display area	376.32 (H) x 301.056 (V) mm
Contrast ratio	1000:1
Brightness	300 Cd/m2
Response time	5ms
Colours	16.7M
Video Synchronization	TTL Positive or Negative
PC Compatible Frequency	30-80KHz (H) / 56-75HZ(v) Max. 1280 x 1024
Viewing Angle	170 (H) / 160 (V)
Adjustable Colour Temperature	9300K / 6500K / 5800K / User
Video Compatibility	Multi-standard for NTSC/PAL/SECAM
Aspect Ratio	4 : 3 Ratio
HDMI	HDCP
Plug & Play	DDC 1 / 2 B
VGA Auto Frequency Correction	Yes
Number of speakers	Right x 1 Left x 1
Sound Demodulation	Stereo. Audio
Mute	Yes
OSD Controls	Contrast, Brightness, Hue, Saturation, Sharpness, Colour Temp, Scaling, Picture Mode, Clock, Phase, H-Position, V-Position, Language, Reset, Sleep Timer, Key lock, Pixel Shift, Auto power recovery, 2D Multi (13) languages, Direct input source select
OSD Language	13 Languages
Volume +/- Power ON/OFF	Yes
INPUT INTERFACE	
Video Interface	15 pin D-sub, Video in x 1 (BNC) BNC Loop through HDMI input x 1
Audio Interface	Audio in x 1, Audio Out x 1 AV Audio (L,R)
Power Interface	AC in x 1
Termination	75 Ohms (Automatic termination)
NB. Specification subject to change without notification	

POWER	
Power Supply	12VDC, 4amp
Voltage	AC100 - 240V 50 / 60Hz
Power Consumption	< 40W
MECHANICAL	
Bezel Thickness	20mm
Vesa Standard Mount	75 x 75 mm
Stand Type	Desktop
Colour	Black
LCD Dimension (Without Base)	390 (W) x 315 (H) x 60 (D) mm
Packing Dimension	440 (W) x 385 (H) x 150 (D) mm
Accessories	Power Supply, Kettle Lead, VGA Cable, Audio cable, User Manual, Remote
Weight	Net Weight: 4.2kgs, Gross Weight: 5.5kg
Work Temperature / Humidity	Temperature: - 10 to 50 °C Humidity: 20 % - 70 %
Certificate	CE / FCC / ROHS



V1.01